



Compact, energy-efficient sounder/ beacon in UV-stabilised ABS/PC blend. Selectable tones and ultra-low power (<50mA) make it ideal for battery systems. Suitable for indoor and outdoor use.

Comes with a 5 year warranty*

Typical applications:

Fire alarms, control panels, vehicle reverse alarms, cranes, telephone lines and food processing plants.

COMBINATION UNITS CE

Sirengo Combination Unit

SPECIFICATIONS

VOLTAGE	9 - 30Vdc 70-260Vac
DUTY CYCLE	Continuous Rated
SOUND OUTPUT	114dB at 1m / 32 Selectable Tones / 3 Stages
SOUND FREQUENCY	420 - 2900Hz
APP. RANGE	600m in ideal conditional (Refer to dB chart)
LIGHT SOURCE	6w LED 16 SMD 360°
CURRENT CONSUMPTION	Amps vary 3-39mA depending on the sound selection
IP RATING	IP 65
WEIGHT	200g
PACKING DIMENSIONS	120mm x 120mm x 130mm

NOTES | Available beacon colours: Red , Green, Blue, Amber and Clear

PRODUCT CODES

Code SFT(*)930 SFT(*)220

Detail 9 - 30Vdc 70 - 260Vac

* x = A for Amber / B for Blue / G for Green / R for Red

TECHNICAL DRAWINGS

All dimensions in mm

